CASIO

Getting Acquainted

Congratulations upon your selection of this CASIO watch. To get the most out of your purchase, be sure to read this manual carefully.

Warning!

- Warning! The measurement functions built into this watch are not intended for use in taking measurements that require professional or industrial precision. Values produced by this watch should be considered as reasonably accurate representations only. The longitude, lunifidal interval, moon age and tide graph data that appear on the display of this watch are not intended for navigation purposes. Always use proper instruments and resources to obtain data for navigation purposes. This watch is not an instrument for calculating low tide and high tide times. The tide graph of this watch is intended to provide a reasonable approximation of tidal movements only.

F

About This Manual



- Depending on the model of your watch, display text appears either as dark figures on a light background or light figures on a dark background. All sample displays in this manual are shown using dark figures on a light background
- Button operations are indicated using the letters shown in the illustration.
 Each section of this manual provides you with the
- information you need to perform operations in each mode. Further details and technical information can be found in the "Reference" section.

E-2

Procedure Lookup

this manual.	
The following is a handy reference list of all the operational procedures contained in	1
Procedure Lookup	

To set the time and date E-9	
To toggle between 12-hour and 24-hour timekeeping E-12	
To toggle the Timekeeping Mode time between DST and Standard Time E-13	
To configure Home Site data E-15	
To specify a date E-19	
To view the time in another city E-22	
To toggle a city code time between Standard Time and Daylight Saving TimeE-22	
To measure times with the stopwatch E-24	
To use Auto-Start E-25	
E-4	

Contents	
General Guide	E-6
Timekeeping	E-8
Tide/Moon Data	E-17
World Time	
Stopwatch	
Countdown Timer	E-26
Alarms	
Illumination	E-39
Reference	
Specifications	
•	

E-3

E-1

To configure the countdown timer	E-29
To use the countdown timer	E-31
To set an alarm time	E-34
To test the alarm	E-36
To turn an alarm on and off	E-37
To turn the Hourly Time Signal on and off	E-38
To illuminate the display	E-39
To specify the illumination duration	E-40
To turn Flash Alert on and off	E-44
To turn the button operation tone on and off	E-45


E-5

World Time Mode

(A

.+WT

General Guide



۹

Tide/Moon Data Mode

-

E-6

A

6

PM indicator

Timekeeping



SAT 6-30

Hour : Minutes Seconds

Use the Timekeeping Mode to set and view the current time and date. time and date.
 The tide graph (page E-42) shows tidal movements for the current date in accordance with the current time as kept in the Timekeeping Mode. B

Important!

Be sure to configure the current time and date, and your Home Site data (data for the site where you use the watch) correctly before using the functions of this watch. See "Home Site Data" (page E-13) for more information. Month - Day

Setting the Time and Date

This watch is preset with UTC differential values that represent each time zone around the globe. Before setting the time, be sure to set the UTC differential for your Home Site first, which is the location where you normally will be using the watch. Note that World Time Mode times (page E-21) are all displayed based on the time and date settings you configure in the Timekeeping Mode.

To set the time and date



1. In the Timekeeping Mode, hold down (A) until the seconds start to flash, which indicates the setting

Be sure to configure the correct UTC differential for your Home Site before configuring any other Timekeeping Mode settings. • See the "UTC Differential/City Code List" at the back

of this manual for information about the UTC differential settings that are supported.

CASIO

2. Press (C) to move the flashing in the sequence shown below to select other settings

Seconds DST UTC Differential Hour Minutes	٦
Flash Alert Day Month Year	1

3. When the setting you want to change is flashing, use D and B to change it as

described below.		
Screen	To do this:	Do this:
50	Reset the seconds to 00	Press D.
DSTOFF Time (0A) and Standard Time (0FF)		Press D.

E-10

To toggle between 12-hour and 24-hour timekeeping In the Timekeeping Mode, press (1) to toggle between 12-hour timekeeping and 24-hour timekeeping. • With the 12-hour format, the P (PM) indicator appears to the left of the hour digits for

- times in the range of noon to 11:59 p.m. and no indicator appears to the left of the hour digits for times in the range of midnight to 11:59 a.m.
 With the 24-hour format, times are displayed in the range of 0:00 to 23:59, without
- Will use 24-nou-non-name and any indicator.
 The 12-hour/24-hour timekeeping format you select in the Timekeeping Mode is
- applied in all other modes

Daylight Saving Time (DST) Setting

Daylight Saving Time (summer time) advances the time setting by one hour from Standard Time. Remember that not all countries or even local areas use Daylight Saving Time

E-12

- The lunitidal interval is the time elapsing between the Moon's transit over a meridian and the next high tide at that meridian. See "Lunitidal Interval" (page E-43) for more information.
- This watch displays lunitidal intervals in terms of hours and minutes
- This Watch displays funitidal intervals in terms of hours and minutes.
 The "Site/Lunitidal Interval Data List" at the back of this manual provides UTC differential and longitude information around the world.
 The following is the initial factory default Home Site data (Tokyo, Japan) when you first purchase the watch and whenever you have the battery replaced. Change these settings to match the area where you normally use the watch.
 UTC differential (+9.0); Longitude (East 140 degrees); Lunitidal interval (5 hours, 20 minute) 20 minutes)

E-14

5. While the setting you want to change is flashing, use (D) and (B) to change it as described below.


Setting	Screen	Button Operations	
Longitude Value	LONG IUNO F	Use () (+) and () (-) to change the setting. • You can specify a value from 0° to 180°, in 1-degree units.	
Longitude (East/West)	190- 1	Use (D) to switch between east longitude ({) and west longitude ({).	
Lunitidal Interval Hours, Minutes	тит С:20	Use \textcircled{D} (+) and \textcircled{B} (-) to change the setting.	

6. Press (A) to exit the setting screen.

E-16

Tide/Moon Data Screens

In the Tide/Moon Data Mode, press (A) to toggle between the Tide Data screen and the Moon Data screen.



Screen	To do this:	Do this:	
+ 90	Specify the UTC differential	Use (D) (+) and (B) (-).	
° 10:58	Change the hour or minutes	Use () (+) and () (-).	
2012 6-30	Change the year, month or day	Use () (+) and () (-).	

See "Daylight Saving Time (DST) Setting" (page E-12) for details about the DST

- See Daylight Saving fine (DS1) Setting (page E-12) for details about the DS1 setting.
 The UTC differential setting range is -12.0 to +14.0, in 0.5-hour units.
 When DST is turned on, the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0, in 0.5 for the UTC differential setting range is -11.0 to +15.0 for the UTC differential setting range is -11.0 to +15.0 for the UTC differential setting range is -11.0 to +15.0 for the UTC differential setting range is -11.0 to +15.0 for the UTC differential setting range is -11.0 to +15.0 for the UTC differential setting range is -11.0 to +15.0 for the UTC differential setting range is -11.0 to +15.0 for the UTC differential setting range is -11.0 to +15.0 for the UTC differential setting range is -11.0 to +15.0 for the UTC differential setting range is -11.0 to +15.0 for the UTC differential setting range is -11.0 to +15.0 for the UTC differential setting 0.5-hour units.
- For information about Flash Alert, see "Flash Alert" (page E-44).
- A Press (a) twice to exit the setting screen.
 The day of the week is displayed automatically in accordance with the date (year, month, and day) settings.

E-11

To toggle the Timekeeping Mode time between DST and Standard Time On/Off status 1. In the Timekeeping Mode, hold down (A) until the seconds start to flash, which indicates the setting



- seconds start to hash, which indicates the setting screen. 2. Press © once and the DST setting screen appears. 3. Press © to toggle between Davight Saving Time (Bf displayed) and Standard Time (BF F displayed). 4. Press (a) twice to exit the setting screen. The DST indicator appears on the Timekeeping, and Tide/Moon Data screens to indicate that Davilght Saving Time is turned on. In the case of the Tide/Moon Data Mode, the DST indicator appears on the Tide Data screen only. screen only.

Home Site Data Moon age, tide graph data, and Tide/Moon Data Mode data will not be displayed properly unless Home Site data (UTC differential, longitude and lunitidal interval) is configured correctly.

E-13

To configure Home Site data Longitude (East/West)
1. In the Timekeeping Mode, hold down (a) until the seconds start to flash, which indicates the setting 7044Cl 1 Ø

Karl In Start Longitude value

- screen. 2. Press \bigcirc twice to display the UTC differential setting screen, and confirm that the setting is correct. If the UTC differential setting is not correct, use \bigcirc (+) and \bigcirc (-) to change it. 3. Press \bigotimes to display the longitude value setting screen. 4. Press \bigotimes to move the flashing in the sequence shown below to select other settings.



E-15



- Tide/Moon data lets you view the moon age for a particular date, and tidal movements for a particular date and time for your Home Site. When you enter the Tide/Moon Data Mode, the data for 6:00 a.m. on the current date appears first. If you suspect that the Tide/Moon data is not correct for appearement block the Time/enseme Mode date.
- some reason, check the Timekeeping Mode data (current time, date, and Home Site settings), and make changes as required.
 See "Tide Graph" (page E-42) for information about the
- See The Graph (page E-42) for information about the tide graph.
 All of the operations in this section are performed in the Tide/Moon Data Mode, which you enter by pressing © (page E-7).

E-17

- While the Tide Data screen is displayed, press (1) to advance to the next hour.
 While the Moon Data screen is displayed, press (1) to advance to the next day.
 You also can specify a particular date (year, month, day) to view its tide data and moon data. See "To specify a date" for more information.
 When you enter the Tide/Moon Data Mode, the screen (tide data or moon data) that was displayed the last time you exited the mode appears first.

To specify a date

Year Month - Dav STIL 2012 6-30 C

1. In the Tide/Moon Data Mode, hold down A until the year setting starts to flash, which indicates the setting screen

2. Press © to move the flashing in the sequence shown below to select the other settings.



Tide/Moon Data

- While a setting is flashing, use () (+) or () (-) to change it.
 You can specify a date in the range of January 1, 2000 to December 31, 2099.
 Press () to exit the setting screen.
 Use () to display either the Tide Data screen or the Moon Data screen.

World Time



selected city

- World Time shows the current time in 48 cities (29 time

- World Time shows the current time in 48 cities (29 time zones) around the world.
 The times kept in the World Time Mode are synchronized with the time being kept in the Timekeeping Mode. If you feel that there is an error in any World Time Mode time, check the UTC differential of your Home Site Data (Home City) and the current setting of the Timekeeping Mode time.
 Select a city code in the World Time Mode to display the current time in any particular time zone around the globe. See the "UTC Differential/City Code List" at the back of this manual for information about the UTC differential settings that are supported.
 All of the operations in this section are performed in the World Time Mode, which you enter by pressing (© (page E-7).
- (page E-7).

E-21

E-20


E-22

To view the time in another city While in the World Time Mode, press D (eastward) to scroll through the city codes (time zones).

affected



- To toggle a city code time between Standard Time and Daylight Saving Time
 1. In the World Time Mode, use ① to display the city code
 (time zone) whose Standard Time/Daylight Saving Time (time zone) whose Standard Time/Daylight Saving Time setting you want to change.
 Hold down (A) to toggle between Daylight Saving Time (DST indicator displayed) and Standard Time (DST indicator not displayed).
 The DST indicator is shown on the World Time Mode screen while Daylight Saving Time is turned on.
 Note that the DST/Standard Time setting affects only the currently displayed city code. Other city codes are not affected.



۹. B STW n'n 0:0000 н S onde Minutes

1/100 second

Stopwatch

- The stopwatch lets you measure elapsed time, split times, and two finishes. It also includes Auto-Start. The display range of the stopwatch is 23 hours, 59 minutes, 59.99 seconds. The stopwatch continues to run, restarting from zero
- I he stopwatch continues to run, restarting from zero after it reaches its limit, until you stop it.
 The stopwatch measurement operation continues even if you exit the Stopwatch Mode.
 Exiting the Stopwatch Mode while a split time is frozen on the display clears the split time and returns to elapsed time measurement.
 All of the operations in this section are performed in the Stopwatch Mode, which you enter by pressing © (page E-7).

E-23

To measure times with the stopwatch

Elapsed Time				
D	→D	→D	→0	→A
Start	Stop	Re-start	Stop	Clear
Split Time				
(D)	→A	→A	→0	→A
Start	Split (SPL displayed)	Split release	Stop	Clear
Two Finishes				
D	→A	→0	→@	→A
Start	Split First runner finishes. Display time of first runner.	Stop Second runner finishes.	Split release Display time of second runner.	Clear

E-24

Countdown Timer



You can set the countdown timer within a range of one minute to 24 hours. An alarm sounds when the countdown reaches zero. The countdown timer also has an auto-repeat feature and a progress beeper that signals the progress of the countdown. • All of the operations in this section are performed in the Countdown Timer Med, which you enfort he pressing

Countdown Timer Mode, which you enter by pressing © (page E-7).

Configuring the Countdown Timer The following are the settings you should configure before actually using the countdown timer. Countdown start time; Auto-repeat on/off; Progress

- See "To configure the countdown timer" (page E-29) for information about setting up the timer.

E-26

E-28

Countdown End Beeper

- The countdown end beeper lets you know when the countdown reaches zero. When the progress beeper is turned off, the countdown end beeper sounds for about 10 seconds, or until you press any button to stop it. When the progress beeper is turned on, the countdown end beeper sounds for about one second.

Progress Beeper

- When the progress beeper is turned on, the watch uses beeps to signal countdown progress as described below. Starting from five minutes before the end of the countdown, the watch emits four

- Starting from hive himules before the end of the countdown, the watch emits four short beeps at the top of each countdown minute.
 30 seconds before the end of the countdown, the watch emits four short beeps.
 The watch emits a short beep for each of the last 10 seconds of the countdown.
 If the countdown start time is six minutes or greater, the watch emits a short beep each second of the final 10 seconds before the five-minute point is reached. Four short beeps are emitted to signal when the five-minute point is reached. ep for

Auto-repeat When auto-repeat is turned on, the countdown restarts automatically from the countdown start time when it reaches zero. When auto-repeat is turned off, the countdown stops when it reaches zero and the

Pressing (D) while an auto-repeat countdown is in progress pauses the current countdown. You can resume the auto-repeat countdown by pressing (D), or you can press (A) to reset to the countdown time starting value.

Countdown Timer Beeper Operations

The watch beeps at various times during a countdown so you can keep informed about the countdown status without looking at the display. The following describes the types of beeper operations the watch performs during a countdown.

E-27

To configure the countdown time



While the countdown start time is on the display in the Countdown Timer Mode, hold down (A) until the current countdown start time starts to flash, which indicates the cuties of the starts of the starts to flash.

countdown start time starts to flash, which indicates the setting screen.
If the countdown start time is not displayed, use the procedure under "To use the countdown timer" (page E-31) to display it.
2. Press © to move the flashing in the sequence shown before out the other action and the setting starts.

below to select other settings Hours Minutes




About Auto-Start

With Auto-Start, the watch performs a 5-second countdown, and stopwatch operation starts automatically when the countdown reaches zero. During the final three seconds of the countdown, a beeper sounds with each second.



- progress will start the stopwatch immediately

E-25





To use Auto-Start

- - While the stopwatch screen is showing all zeros in the Stopwatch Mode, press (a).
 This displays a 5-second countdown screen.
 To return to the all zeros screen, press (a) again.
 Press (b) to start the countdown.
 When the countdown reaches zero, a tone sounds and a stopwatch timing operation starts automatically.

 - stopwatch timing operation starts automatically. Pressing D while the Auto-Start countdown is in

3. When the setting you want to change is flashing, use (D) and (B) to change it as described below

Setting	Screen	Button Operation		
Hours, Minutes	0:00	Use \textcircled{D} (+) and \textcircled{B} (-) to change the setting.		
Auto-repeat	Press (D) to toggle auto-repeat on (
Progress Beeper	JOFF	Press \textcircled{D} to toggle the progress beeper on $(\textcircled{D}M)$ and off $(\textcircled{D}FF)$.		

• To specify a countdown start time of 24 hours, set []:[][. 4. Press (A) to exit the setting screen. • You also can perform steps 1 and 2 of the above procedure whenever you need to view the current auto-repeat and progress beeper settings.

displayed

(D)

E-30

Alarms

E-32

(A

E-34

E-36

Alarm Operation



To set an alarm time

AL2

12:00

This watch has three independent multi-function alarms (including one snooze alarm). When an alarm is turned on, the alarm tone sounds when the alarm time is reached. You also can turn on an Hourly Time Signal that causes the watch to beep twice every hour on the hour. There are three alarm screens: \mathbf{R}_{1} , \mathbf{RL}_{2} , and \mathbf{SNZ} (snooze). The Hourly Time Signal screen is indicated by \mathbf{STR}_{1}

All of the operations in this section are performed in the Alarm Mode, which you enter by pressing © (page E-7).

1. In the Alarm Mode, use D to scroll through the alarm

screens until the one whose time you want to set is

D

AL 1

SIG

The snooze alarm operation repeats every five minutes.
After you select an alarm screen, hold down (a) until the hour setting of the alarm time starts to flash, which indicates the setting screen.
This operation turns on the currently selected alarm automatically.

Alarm Operation The alarm tone sounds at the preset time for 10 seconds, regardless of the mode the watch is in. In the case of the snooze alarm, the alarm operation is performed a total of seven times, every five minutes, until you turn the alarm off (page E-37). • Alarm and Hourly Time Signal operations are performed in accordance with the Timekeeping Mode time. • To stop the alarm tone after it starts to sound, press any button. • Performing any one of the following operations during a 5-minute interval between snooze alarms cancels the current snooze alarm operation. Displaying the Timekeping Mode setting screen (page E-9) Displaying the SNZ setting screen (page E-34)

AL2

SNZ

D

To use the countdown time



Press D while in the Countdown Timer Mode to start the countdown timer.

The countdown timer operation continues even if you

- Ine countown timer operation continues even if you exit the Countdown Timer Mode.
 Press

 while a countdown operation is in progress to pause it. Press
 B again to resume the countdown.
 To stop a countdown operation completely, first pause it (by pressing

 b), and then press
 c). This returns the countdown time to its starting value.

E-31

Alarm Types

The alarm type is determined by the settings you make, as described below. Daily alarm

Set the hour and minutes for the alarm time. This type of setting causes the alarm to sound everyday at the time you set.

• Date alarm Set the month, day, hour and minutes for the alarm time. This type of setting causes the alarm to sound at the specific time, on the specific date you set.

1-Month alarm

Set the month, hour and minutes for the alarm time. This type of setting causes the alarm to sound everyday at the time you set, only during the month you set.

Monthly alarm

Set the day, hour and minutes for the alarm time. This type of setting causes the alarm to sound every month at the time you set, on the day you set.

E-33

3. Press \bigcirc to move the flashing in the sequence shown below to select other settings

┍→[Hour] →[Minutes]→[Month	}→ [Day	Ъ

4. While a setting is flashing, use (D) and (B) to change it as described below.

Screen	To do this:	Do this:
16:00	Change the hour and minutes	Use () (+) and () (-). •With the 12-hour format, set the time correctly as
	Change the month and day	 a.m. or p.m. (P indicator). To set an alarm that does not include a month and/ or day, set - for each setting.

5. Press (A) to exit the setting screen.

E-35

To turn an alarm on and off



1. In the Alarm Mode, use (i) to select an alarm screen.
2. Press (ii) to toggle the selected alarm between on and off.
Turning on an alarm displays the alarm on indicator on its Alarm Mode screen (AL 1, AL2, or SNZ).
In all modes, the alarm on indicator is shown for any alarm the average the readers.

- alarm that is currently turned on. The alarm on indicator flashes while the alarm is
- The atam of indicator hashes while the atam is sounding.
 The snozze alarm indicator flashes while the snozze alarm is sounding and during the 5-minute intervals between alarm operations.

E-37

To test the alarm In the Alarm Mode, hold down (1) to sound the alarm.



To turn the Hourly Time Signal on and off 1. In the Alarm Mode, use (1) to select the Hourly Time Signal (SIG). 2. Press (3) to toggle it on and off. • The Hourly Time Signal on indicator is shown on the display in all modes while this function is turned on.

Illumination

This watch has an EL (electro-luminescent) panel that causes the entire display to glow for easy reading in the dark. • See "Illumination Precautions" (page E-48) for other important information about

using illumination.

To illuminate the display In any mode (except when a setting screen is on the display), press (B) to turn on illumination.

 You can use the procedure below to select either 1.5 seconds or 3 seconds as the illumination duration. When you press (B), the illumination will remain on for about 1.5 seconds or 3 seconds, depending on the current illumination duration setting



CASIO

To specify the illumination duration 1. In the Timekeeping Mode, hold down (A) until the seconds start to flash, which indicates the setting screen.



E-40

E-42

Flash Alert

Ċ.

C

E-44

To turn Flash Alert on and off

יידעייי גאינאיג: גאינאיג:

ര

Tide Graph

н

High Tide

2. While the seconds are flashing, press (B) to toggle the setting between 1.5 seconds (♦) and 3 seconds (♦). 3. Press (A) twice to exit the setting screen.

The Tide Graph has six graphic segments, each of which indicates a different tide level. The current tide level is indicated by the displayed graphic segment.

. Low Tide

(Falling

Tide)

L .

When Flash Alert is turned on, the illumination flashes for the alarms, the Hourly Time Signal, the countdown alarm, and stopwatch auto start.

screen

(Rising Tide)

In the Timekeeping Mode, hold down (A) until the seconds start to flash, which indicates the setting

2. Press © eight times to display the Flash Alert setting

Press (D) to toggie russ in version (J) in an end of (J).
 Press (A) twice to exit the setting screen.
 The Flash Alert setting you select with the above procedure is applied in all modes.
 When Flash Alert is on, \$\frac{y}{2} fl appears for about one second whenever you enter the Stopwatch, Countdown Timer, or Alarm Mode.

Reference

This section contains more detailed and technical information about watch operation. It also contains important precautions and notes about the various features and functions of this watch.

Moon Age

The Moon goes through a regular 29.53-day cycle. During each cycle, the Moon appears to wax and wane as the relative positioning of the Earth, the Moon, and the Sun changes. The greater the angular distance between the Moon and the Sun,* the more we see illuminated. * The angle to the Moon in relation to the direction at which the Sun is visible from the

This watch performs a rough calculation of the current Moon age starting from day 0 of the moon age cycle. Since this watch performs calculations using integer values only (no fractions), the margin for error of the displayed Moon age is ± 1 day.

E-41

Tidal Movements

Tidal Movements Tides are the periodic rise and fall of the water of oceans, seas, bays, and other bodies of water caused mainly by the gravitational interactions between the Earth, Moon and Sun. Tides rise and fall about every six hours. The tide graph of this watch indicates tidal movement based on the Moon's transit over a meridian and the lumitidal interval. The lumitidal interval differs according to your current location, so you must specify a lumitidal interval on oder to obtain the correct tide graph readings. The tide graph displayed by this watch is based on the current Moon age. Remember that the margin for error of the Moon age displayed by this watch is ± 1 day. The greater the error in a particular Moon age, the greater the error in the resulting tide graph.

Lunitidal Interval

Lunitidal Interval Theoretically, high tide is at the Moon's transit over the meridian and low tide is about six hours later. Actual high tide occurs somewhat later, due to factors such as viscosity, friction, and underwater topography. Both the time differential between the Moon's transit over the meridian until high tide and the time differential between the Moon's transit over the meridian until low tide are known as the "lunitidal interval". When setting the lunitidal interval for this watch, use the time differential between the Moon's transit over the meridian until high tide. E43

E-43

Button Operation Tone



The button operation tone sounds any time you press one of the watch's buttons. You can turn the button operation tone on or off as desired. • Even if you turn off the button operation tone, the

alarms, the Hourly Time Signal, the countdown alarm, and stopwatch auto start all operate normally.

To turn the button operation tone on and off In any mode (except when a setting screen is on the display), hold down © to toggle the button operation tone on (nutle indicator not displayed) and off (mute indicator

displayed). . Holding down (C) to turn the button operation tone on or off also causes the watch's

current mode to change. • The mute indicator is displayed in all modes when the button operation tone is turned off

The UTC differential is a value that indicates the time difference between a reference point in Greenwich, England and the time zone where a city is located.
The letters UTC is the abbreviation for Coordinated Universal Time, which is the

world wide scientific standard of timekeeping. It is based upon carefully maintained atomic (easium) clocks that keep time accurately to within microseconds. Leap seconds are added or subtracted as necessary to keep UTC in sync with the Earth's rotation.

Timekeeping
Resetting the seconds to 00 while the current count is in the range of 30 to 59 causes the minutes to be increased by 1. In the range of 00 to 29, the seconds are reset to 00 without changing the minutes.
The year can be set in the range of 2000 to 2099.
The watch's built-in full automatic calendar makes allowances for different month learthe of the date the date the scheader be are resent to be an extended to

lengths and leap years. Once you set the date, there should be no reason to change it except after you have the watch's battery replaced.

E-45

E-47

Auto Return Features

- If you leave the watch in the Alarm Mode or Tide/Moon Data Mode for two or three minutes without performing any operation, it changes to the Timekeeping Mode automatically.
- If you leave a screen with flashing digits on the display for two or three minutes without performing any operation, the watch exits the setting screen automatically.

Scrolling

The (B and (D) buttons are used in various modes and setting screens to scroll through data on the display. In most cases, holding down these buttons during a scroll operation scrolls at high speed.

Initial Screens

When you enter the World Time or Alarm Mode, the data you were viewing when you last exited the mode appears first.

E-46

World Time

- The seconds count of the World Time is synchronized with the seconds count of the Timekeeping Mode.
 All World Time Mode times are calculated from the current time in the Timekeeping Mode using UTC time differential values.

Illumination Precautions

- . The electro-luminescent panel that provides illumination loses power after very long
- Use.
 Illumination may be hard to see when viewed under direct sunlight.
 The watch may emit an audible sound whenever the display is illuminated. This is due to vibration of the EL panel used for illumination, and does not indicate
- malfunction
- Illumination turns off automatically whenever an alarm sounds.
 Frequent use of illumination runs down the battery.

Specifications

- Accuracy at normal temperature: ± 30 seconds a month Timekeeping: Hour, minutes, seconds, p.m. (P), month, day, day of the week Time format: 12-hour and 24-hour Calendar system: Full Auto-calendar pre-programmed from the year 2000 to 2099 Other: Daylight Saving Time (summer time)/Standard Time; Home Site data settings (UTC differential, longitude, lunitidal interval) Tide/Moon Data: Moon age for specific date; Tide level for specific date and time World Time: 48 cities (29 time zones) Other: Daylight Saving Time/Standard Time Stopwatch:
- Stopwatch:

- Measuring unit: 1/100 second Measuring capacity: 23:59' 59.99" Measuring modes: Elapsed time, split time, two finishes Other: Auto-Start





UTC

Countdown Timer: Measuring unit: 1 second Input range: 1 minute to 24 hours (1-minute increments and 1-hour increments) Other: Auto-repeat timing; Progress beeper Alarms: 3 multi-function alarms (with 1 snoze alarm); Hourly Time Signal Illumination: EL (electro-luminescent panel); Selectable illumination duration Other: Button operation tone on/off; Flash alert

Battery: One lithium battery (Type: CR1616) Approximately 3 years on type CR1616 (10 seconds of alarm operation per day (with flash alert), one countdown timer operation (with progress beeper and flash alert) per week, one stopwatch operation (with auto start and flash alert) per week, 1.5 seconds of illumination per day)

Frequent use of the light shortens the battery life.

E-50

UTC Differential/City Code List

City Code	City	UTC Differential	Other major cities in same time zone
PPG	Pago Pago	-11	
HNL	Honolulu	-10	Papeete
ANC	Anchorage	-9	Nome
YVR	Vancouver		
SFO	San Francisco] _8	Las Vegas, Seattle/Tacoma, Dawson City
LAX	Los Angeles	1	
DEN	Denver	-7	Edmonton, El Paso
MEX	Mexico City	-6	Houston, Dallas/Fort Worth, New Orleans, Winnipeg
CHI	Chicago	1 -0	
MIA	Miami	-5	Montreal, Detroit, Boston,
NYC	New York	1 -5	Panama City, Havana, Lima, Bogota
CCS*	Caracas	-4	La Paz, Santiago, Port Of Spain
YYT	St. Johns	-3.5	
RIO	Rio De Janeiro	-3	Sao Paulo, Buenos Aires, Brasilia, Montevideo
RAI	Praia	-1	
LIS	Lisbon	0	Dublin, Casablanca, Dakar, Abidian
LON	London	1 0	Dubiin, Casabianca, Dahar, Ablujan

L-2

City Code	City	UTC Differential	Other major cities in same time zone		
DAC	Dhaka	+6			
RGN	Yangon	+6.5			
BKK	Bangkok	+7	Phnom Penh, Hanoi, Vientiane, Jakarta		
SIN	Singapore				
HKG	Hong Kong	+8	Kuala Lumpur, Taipei, Manila, Perth, Ulaanbaatar		
BJS	Beijing	1			
SEL	Seoul	+9	Pyongyang		
TYO	Tokyo		ryongyang		
ADL	Adelaide	+9.5	Darwin		
GUM	Guam	+10	Melbourne, Rabaul		
SYD	Sydney	+10			
NOU	Noumea	+11	Port Vila		
WLG	Wellington	+12	Christchurch, Nadi, Nauru Island		

Based on data as of December 2010.
 In December 2007, Venezuela changed its offset from -4 to -4.5. Note, however, that this watch displays an offset of -4 (the old offset) for the CCS (Caracas, Venezuela) city code.

L-4

	UTC D	ifferential		Lunitidal
Site	Standard Time	DST/ Summer Time	Longitude	Interval
Honolulu	-10.0	-9.0	158°W	3:40
Jakarta	+7.0	+8.0	107°E	0:00
Jeddah	+3.0	+4.0	39°E	6:30
Karachi	+5.0	+6.0	67°E	10:10
Kona, Hawaii	-10.0	-9.0	156°W	4:00
Lima	-5.0	-4.0	77°W	5:20
Lisbon	+0.0	+1.0	9°W	2:00
London	+0.0	+1.0	0°E	1:10
Los Angeles	-8.0	-7.0	118°W	9:20
Maldives	+5.0	+6.0	74°E	0:10
Manila	+8.0	+9.0	121°E	10:30
Mauritius	+4.0	+5.0	57°E	0:50
Melbourne	+10.0	+11.0	145°E	2:10
Miami	-5.0	-4.0	80°W	7:30
Noumea	+11.0	+12.0	166°E	8:30

1	 -6



City Code	City	UTC Differential	Other major cities in same time zone			
BCN	Barcelona					
PAR	Paris	1	Amsterdam, Algiers, Hamburg, Frankfurt, Vienna, Madrid,			
MIL	Milan	+1	Stockholm			
ROM	Rome	1				
BER	Berlin	1				
ATH	Athens					
JNB	Johannesburg	1				
IST	Istanbul	+2	Helsinki, Beirut, Damascus, Cape Town			
CAI	Cairo	1				
JRS	Jerusalem	1				
MOM	Moscow	+3	Kuusia Diusella Astau Astalia Albaha Majashi			
JED	Jeddah	1 +3	Kuwait, Riyadh, Aden, Addis Ababa, Nairobi			
THR	Tehran	+3.5	Shiraz			
DXB	Dubai	+4	Abu Dhabi, Muscat			
KBL	Kabul	+4.5				
KHI	Karachi	. 5				
MLE	Male	+5				
DEL	Delhi	+5.5	Mumbai, Kolkata, Colombo			

L-3

Site/Lunitidal Interval Data List

	UTC Di	UTC Differential		Lunitidal
Site	Standard Time	DST/ Summer Time	Longitude	Interval
Anchorage	-9.0	-8.0	149°W	5:40
Bahamas	-5.0	-4.0	77°W	7:30
Baja, California	-7.0	-6.0	110°W	8:40
Bangkok	+7.0	+8.0	101°E	4:40
Boston	-5.0	-4.0	71°W	11:20
Buenos Aires	-3.0	-2.0	58°W	6:00
Casablanca	+0.0	+1.0	8°W	1:30
Christmas Island	+14.0	+15.0	158°W	4:00
Dakar	+0.0	+1.0	17°W	7:40
Gold Coast	+10.0	+11.0	154°E	8:30
Great Barrier Reef, Cairns	+10.0	+11.0	146°E	9:40
Guam	+10.0	+11.0	145°E	7:40
Hamburg	+1.0	+2.0	10°E	4:50
Hong Kong	+8.0	+9.0	114°E	9:10

L-5

	UTC D	UTC Differential		Lunitidal
Site	Standard Time	DST/ Summer Time	Longitude	Interval
Pago Pago	-11.0	-10.0	171°W	6:40
Palau	+9.0	+10.0	135°E	7:30
Panama City	-5.0	-4.0	80°W	3:00
Papeete	-10.0	-9.0	150°W	0:10
Rio De Janeiro	-3.0	-2.0	43°W	3:10
Seattle	-8.0	-7.0	122°W	4:20
Shanghai	+8.0	+9.0	121°E	1:20
Singapore	+8.0	+9.0	104°E	10:20
Sydney	+10.0	+11.0	151°E	8:40
Tokyo	+9.0	+10.0	140°E	5:20
Vancouver	-8.0	-7.0	123°W	5:10
Wellington	+12.0	+13.0	175°E	4:50

•Based on data as of 2003.

L-7